Cisco Industry Marketing Team
Cisco Systems, Inc.
170 W. Tasman Drive
San Jose, California 95134-1706
USA
http://www.cisco.com/go/industrysolutions
Tel: 408 526-4000 408 526-7660
Fax: 408 526-4100
Cisco Systems International BV
Haarlerbergpark
Haarlerbergweg 13-19
1101 CH Amsterdam, The Netherlands
www-europe.cisco.com
Tel: +31 0 20 357 1000
Fax: +31 0 20 357 1100
Cisco Systems, Australia, Headquarters Level 9
Cisco House, 654 Pacific Highway
St Leonards, NSW 2065
Australia
www.cisco.com.au
Tel: +61 2 8448 7068
Fax: +61 2 8448 7060

Table of Contents

1.0 Introduction
2.0 Characteristics of Infrastructure
3.0 Principles and Goals
4.0 Big Architectural Framework, Overview
5.0 Functional Services Model
6.0 Architectural Framework, Reference Model
7.0 Scenarios
8.0 Glossary
9.0 Index

1.0 Introduction

1.1 The National Information Infrastructure

In "The National Information Infrastructure: Agenda for Action" (Washington, DC: Government Printing Office, 1993), the Clinton Administration lists 9 goals for the National Information Infrastructure (NII). Among the goals are the promotion of private investment, the extension of universal service, the promotion of rapid technological innovation, and the dissemination of new services throughout the nation. The document also lists 5 principles that will guide the Administration in its support of the development of the NII. These principles include promoting competition, providing access to "information infrastructure" for all people, and ensuring that the NII meets a wide variety of social and economic needs. The document also states that the NII should be dynamic and flexible so that it can keep pace with changes in technology, markets, and public needs.

The NII document can be viewed as the aggregate of all information networks, services, and applications. It also includes the people who create the information that flows over the networks, the companies that build the networks and develop the applications, and the people who use the networks and applications to create, distribute, and consume information in their homes, businesses, schools, and communities.

Achieving the vision of goals and principles outlined in the NII document will be a complex undertaking. It will require the cooperation of many different types of people and organizations. It will also require a framework on which to hang the various pieces of technology, standards, and information. This document is intended to be that framework.

1.2 NII Architectural Overview

The NII architecture can be viewed as a collection of interconnected, value-added networks of information servers, clients, and supporting infrastructure. Information servers will be distributed throughout the network. Some will be open to the public, others will be closed, and others will be open only to those who have paid for the information they wish to access. Clients will be able to access information from servers on the network, process it, and present it to the user. Clients will be able to locate information of interest to their users by accessing directories of information that describe what information is available on the various servers on the network. Supporting infrastructure will include the network hardware and software that interconnects the various information servers and clients, directory servers, and other supporting infrastructure.

Similarly, pieces of the NII can be viewed as a collection of interconnected, value-added networks of information servers, clients, and supporting infrastructure. Some of these networks will be open to the public, others will be closed to all but paying customers, and others will be open only to those who have paid for the information they wish to access. Each of these networks will have its own set of information servers, clients, directories, and supporting infrastructure.

The Cisco Internet Business Solutions Group (IBSG) has chosen to use the term "Cloud" to describe a network that is open to the public and supports a wide variety of protocols and those applications and services. We expect that the Internet will be the most common example of a Cloud, but there will be others. Some will be local, others will be regional, others will be national, others will be global, and others will be some combination of the above. Some will be open to all comers, others will be open only to those who have paid for the privilege of using the network. Some will be open to all comers but will charge for some services. Some will be open to all comers but will charge for all services. Some will be open only to those who have paid for the privilege of using the network, but will charge for some services. Some will be open only to those who have paid for the privilege of using the network, but will charge for all services.

The Internet Cloud will be the most common example of a Cloud, but there will be many others. The Internet Cloud will be a collection of interconnected, value-added networks of information servers, clients, and supporting infrastructure

the Transport protocol (port 21, Ordinary) offers, and relating an appropriate Transport protocol (port 21, Ordinary) to the application. The Transport protocol (port 21, Ordinary) offers a set of services to the application, and the application selects the appropriate service.

We also discuss scenarios for cases with unbalanced channels that present problems for the Internet Protocol. The application layer protocol (port 21, Ordinary) offers a set of services to the application layer, and the application selects a service and sends the user-defined application data to Transport protocol (port 21, Ordinary).

Transport protocol (port 21, Ordinary) uses one of the Transport protocol (port 21, Ordinary) services to transport the application data. Transport protocol (port 21, Ordinary) offers a set of services to the application layer, and the application selects a service and sends the application data to Transport protocol (port 21, Ordinary). Transport protocol (port 21, Ordinary) uses one of the Internet Protocol services to transport the application data.

Internet Protocol offers a set of services to the Transport protocol (port 21, Ordinary) and the Transport protocol (port 21, Ordinary) selects a service and sends the application data to Internet Protocol. Internet Protocol uses one of the Ethernet services to transport the application data. Ethernet offers a set of services to the Internet Protocol, and the Internet Protocol selects a service and sends the application data to Ethernet.

The Ethernet frame is made up of various communications bytes including Ethernet header, Internet Protocol header, Transport protocol (port 21, Ordinary) header, and application data. The application layer protocol (port 21, Ordinary) offers a set of services to the application, and the application selects a service and sends the application data to Transport protocol (port 21, Ordinary). Transport protocol (port 21, Ordinary) uses one of the Internet Protocol services to transport the application data.

Internet Protocol offers a set of services to the Transport protocol (port 21, Ordinary) and the Transport protocol (port 21, Ordinary) selects a service and sends the application data to Internet Protocol. Internet Protocol uses one of the Ethernet services to transport the application data. Ethernet offers a set of services to the Internet Protocol, and the Internet Protocol selects a service and sends the application data to Ethernet.

Ethernet receives and transmits datagrams and uses sounds as symbols to transmit data. Ethernet uses a set of sounds to transmit data to other Ethernet users. Ethernet sounds are easy to hear, and the sounds are easy to understand. Ethernet sounds are easy to understand because they are made up of a set of sounds that are easy to understand. Ethernet sounds are easy to understand because they are made up of a set of sounds that are easy to understand.

Frame sound is also a sentence that relates and distributes a combination of Ethernet sounds to the receiver. Ethernet sounds are easy to understand because they are made up of a set of sounds that are easy to understand. Ethernet sounds are easy to understand because they are made up of a set of sounds that are easy to understand. These sounds are easy to understand because they are made up of a set of sounds that are easy to understand.

The computer uses a numerical system to transmit application data. We refer to the numerical system used by computers as a binary system. Some people are familiar with the binary system, but others are not. The binary system is a numerical system that uses only two digits, 0 and 1. The binary system is a numerical system that uses only two digits, 0 and 1. The binary system is a numerical system that uses only two digits, 0 and 1. The binary system is a numerical system that uses only two digits, 0 and 1. The binary system is a numerical system that uses only two digits, 0 and 1.

7.2 Scenario 2: An Education Example

This scenario, an educational technology company in a small-scale school district, provides a cloud-based learning management system (LMS) that allows school districts and teachers to create, store, and deliver digital lessons and assessments. The company's LMS is used by teachers in classrooms with students ranging from elementary to high school. The LMS allows teachers to upload lesson plans, quizzes, and multimedia resources, track student progress, and communicate with students and parents. The system has several features designed to enhance classroom learning and support teacher workflows.

Teachers can create and manage digital lesson plans, assign homework, and grade assignments directly within the platform. The LMS also includes a gradebook that automatically calculates student grades based on teacher-defined criteria. The system supports various assessment types, including multiple-choice questions, essays, and project-based assignments. The LMS also allows teachers to create discussion forums and chat rooms for students to collaborate on projects and ask questions.

The system offers a mobile app for iOS and Android that allows students and teachers to access the LMS from their smartphones and tablets. The mobile app provides push notifications for new assignments, grades, and messages, ensuring that users are always informed about important updates. The app also allows students to submit assignments and take quizzes on the go, making it convenient for students to complete their work outside the classroom.

While this, This year profit, in short order, was years developed for software development and deployment, the company has been facing increasing competition from other edtech companies. To stay ahead of the curve, the company is considering adding new features to its LMS, such as gamification elements and adaptive learning tools. The company is also exploring the possibility of expanding its LMS to other markets, such as higher education and corporate training.

Through the educational software development, Tim learns about more complex topics, such as the Transport protocol (port 21, Ordinary) and the Internet Protocol, and how these protocols are used to transmit data over the Internet.

Alexandra: Tim investigates connectivity issues. Broadband service in Alexandra's neighborhood has been slow and unreliable, causing frustration among residents who rely on the Internet for work, education, and entertainment. Tim decides to investigate the issue and find a solution for his neighbors.

To make sense of the application layer protocol (port 21, Ordinary), Tim creates a set of sounds that represent different types of data, such as a beep for ordinary sounds or classified sentences or sentence breaks. Some sounds are easy to hear, and others are difficult to hear. The application layer protocol (port 21, Ordinary) uses a set of sounds to transmit data to other users. The application layer protocol (port 21, Ordinary) uses a set of sounds to transmit data to other users. The application layer protocol (port 21, Ordinary) uses a set of sounds to transmit data to other users. The application layer protocol (port 21, Ordinary) uses a set of sounds to transmit data to other users.

Tim creates a set of sounds that represent the Transport protocol (port 21, Ordinary). The Transport protocol (port 21, Ordinary) uses a set of sounds to transmit data to other users. The Transport protocol (port 21, Ordinary) uses a set of sounds to transmit data to other users. The Transport protocol (port 21, Ordinary) uses a set of sounds to transmit data to other users. The Transport protocol (port 21, Ordinary) uses a set of sounds to transmit data to other users.

Tim creates a set of sounds that represent the Internet Protocol. The Internet Protocol uses a set of sounds to transmit data to other users. The Internet Protocol uses a set of sounds to transmit data to other users. The Internet Protocol uses a set of sounds to transmit data to other users. The Internet Protocol uses a set of sounds to transmit data to other users.

Tim creates a set of sounds that represent Ethernet. Ethernet uses a set of sounds to transmit data to other users. Ethernet uses a set of sounds to transmit data to other users. Ethernet uses a set of sounds to transmit data to other users. Ethernet uses a set of sounds to transmit data to other users.

Tim creates a set of sounds that represent the application data. The application data uses a set of sounds to transmit data to other users. The application data uses a set of sounds to transmit data to other users. The application data uses a set of sounds to transmit data to other users. The application data uses a set of sounds to transmit data to other users.

Tim creates a set of sounds that represent the Ethernet frame. The Ethernet frame uses a set of sounds to transmit data to other users. The Ethernet frame uses a set of sounds to transmit data to other users. The Ethernet frame uses a set of sounds to transmit data to other users. The Ethernet frame uses a set of sounds to transmit data to other users.

Tim creates a set of sounds that represent the Ethernet header. The Ethernet header uses a set of sounds to transmit data to other users. The Ethernet header uses a set of sounds to transmit data to other users. The Ethernet header uses a set of sounds to transmit data to other users. The Ethernet header uses a set of sounds to transmit data to other users.

Tim creates a set of sounds that represent the Internet Protocol header. The Internet Protocol header uses a set of sounds to transmit data to other users. The Internet Protocol header uses a set of sounds to transmit data to other users. The Internet Protocol header uses a set of sounds to transmit data to other users. The Internet Protocol header uses a set of sounds to transmit data to other users.

Tim creates a set of sounds that represent the Transport protocol (port 21, Ordinary) header. The Transport protocol (port 21, Ordinary) header uses a set of sounds to transmit data to other users. The Transport protocol (port 21, Ordinary) header uses a set of sounds to transmit data to other users. The Transport protocol (port 21, Ordinary) header uses a set of sounds to transmit data to other users. The Transport protocol (port 21, Ordinary) header